

SNOW GUARD BRACKET  
ATTACHED TO BASE PLATE  
WITH S.S. NUTS AND  
NEOPRENE WASHERS



FTR MEMBRANE TARGET  
FLASHING CENTERED  
OVER BASE PLATE, HOT  
AIR WELD CONTINUOUS  
(MIN. 2" WIDE WELD)

SNOW GUARD BASE PLATE,  
FASTEN INTO WOOD BLOCKING  
WITH COUNTERSUNK  
FASTENERS

APPLY FTR 101 SEALANT  
AROUND STUDS OF BASE  
PLATE PRIOR TO  
INSTALLING TARGET  
FLASHING

FTR REINFORCED  
MEMBRANE PROTECTION  
LAYER AT BASE PLATE  
LOCATION, HOT AIR  
WELD CONTINUOUS  
(MIN. 2" WIDE WELD)

FTR OR FTR-FB MEMBRANE  
(PER SPECIFICATION)

WOOD BLOCKING FOR SNOW  
GUARD BASE PLATE  
ATTACHMENT, SECURELY  
FASTENED TO ROOF DECK

INSULATION ATTACHED PER  
SPECIFICATION REQUIREMENTS

ROOF DECK



GENERAL REFERENCE:  
"FTR GS 01/21"

APPLICABLE SYSTEMS:  
"FTR AD 01/21"  
"FTR SMRP 01/21"

SNOW GAURD "NEW CONSTRUCTION"

REVISES DETAIL  
ALL PREVIOUS

ISSUE DATE  
02-10-14

DRAWING NUMBER  
FTR-SGNC