



SAFETY DATA SHEET

FiberTite® FTR-490 Adhesive

Rev. Date: 21 Apr 2021

SECTION 1. PRODUCT & COMPANY INFORMATION

Product Name: FTR-490 Roofing Adhesive

Recommended Use: Roofing adhesive

Manufacturer: SEAMAN CORPORATION
1000 Venture Blvd.
Wooster, OH 44691 USA
PHONE: (330) 262-1111
www.seamancorp.com

24-HR EMERGENCY (Chemtrec)
U.S./Canada: (800) 424-9300
International: +1 703 527-3887

SECTION 2. HAZARDS IDENTIFICATION

Pictograms:



Signal Word: DANGER

GHS Classification:

Flammable Liquid – Category 4
Acute Toxicity - Oral - Category 3
Acute Toxicity - Dermal - Category 3
Acute Toxicity - Inhalation - Category 3
Aspiration Hazard – Category 1
Skin Irritation – Category 2
Eye Irritation – Category 2A
Toxic to Reproduction – Category 2
Specific Target Organ Toxicity (Single Exposure) – Category 2
Specific Target Organ Toxicity (Repeated Exposure) – Category 2

Hazard Statements:

H227 Combustible liquid
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H331 Toxic if inhaled.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.
H370 Causes damage to organs (CNS)
H373 May cause damage to organs (CNS) through prolonged or repeated exposure.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapors.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves and eye protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P311 IF exposed or concerned: Call a POISON CENTER or doctor.
P308 + P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER or doctor if you feel unwell.
P330 Rinse mouth.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P361 + P364 Take off immediately all contaminated clothing and wash it before reuse.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry chemical, CO2, or foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P235 Keep cool.

Disposal:

P501 Dispose of contents/container in accordance with local/regional/national regulations

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS No.</u>	<u>% by weight</u>
Toluene	108-88-3	3-10
Methanol	67-56-1	1-5

SECTION 4. FIRST AID MEASURES

Inhalation: Move to fresh air. Seek medical attention if symptoms persist.
Skin Contact: Wash exposed skin with soap and water. Do not use solvents or thinners. If irritation develops or persists, seek medical attention.
Eye Contact: Flush eyes with plenty of water for at least 15 minutes. Seek medical attention.
Ingestion: Seek medical attention. Do not induce vomiting.

SECTION 5. FIRE FIGHTING MEASURES

Flammable Properties: Material is combustible.
Suitable Extinguishing Media: alcohol resistant foam, CO2, powders, water spray
Products of Combustion: Carbon monoxide and carbon dioxide
Protection of Firefighters: Firefighters should wear self-contained breathing apparatus and full fire-fighting turnout gear. No special procedures are expected to be necessary for this product.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8.
Environmental Precautions: No special procedures necessary
Methods for Containment: No special procedures necessary
Methods for Clean-up: No special procedures necessary

SECTION 7. HANDLING AND STORAGE

Handling: Use protective equipment recommended in Section 8. Use only in well ventilated area. Eliminate any source of ignition. Ground and bond all equipment when handling. Wash hands after contact.
Storage: Storage temperature 60°F to 95°F (15°C to 35°C). Shelf life one year from manufacture date. Avoid heating or direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES

COMPONENT	OSHA (PEL)	ACGIH (TLV)	NIOSH (REL)	COMMENTS
Toluene (108-88-3)	200 ppm (590 mg/m ³) TWA; 300 ppm STEL	20 ppm TWA	-	
Methanol (67-56-1)	200 ppm (260 mg/m ³) TWA	200 ppm (262 mg/m ³) TWA; 250 ppm (328 mg/m ³) STEL	200 ppm (260 mg/m ³) TWA; 250 ppm (325 mg/m ³) STEL	

PERSONAL PROTECTIVE EQUIPMENT

Engineering Controls: Provide local exhaust ventilation
Eye/Face: Wear safety glasses
Skin: Wear chemical resistant protective gloves
Respiratory: If exposure limits are exceeded, NIOSH approved respiratory protection must be provided
General Hygiene: Wash hands with soap and water after handling material.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White liquid	Odor: Solvent
Odor threshold: Not available	pH: Not available
Melting/Freezing Point: Not available	Boiling Point: >100°C (212°F)
Flash Point: 91.1°C (196°F)	Evaporation Rate: >1.0 (butyl acetate=1)
Flammability: Category 4	LFL/UFL: 1.2% / 7.1% (toluene only)
Vapor Pressure: Not determined	Vapor Density: Greater than air
Relative Density: 1.078 (8.99 lb/gal)	Solubility: Soluble in water
Partition Coefficient K_{ow}: Not available	Auto-Ignition Temp.: 725-997°F
Decomposition Temp.: Not applicable	Viscosity: Not available

VOC Content: 179 g/L (EPA Method 24)
 Photochemically reactive VOC: 109.7 g/L
 10.1% by weight HAP

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability:	Stable at recommended storage and handling conditions
Conditions to Avoid:	Sources of ignition
Incompatible Materials:	Oxidizing agents, strong acids, strong bases
Hazardous Decomposition:	Carbon monoxide, carbon dioxide
Hazardous Reactions:	Will not occur

SECTION 11. TOXICOLOGY INFORMATION

POTENTIAL HEALTH EFFECTS:

Summary:	Eye and skin irritation
Inhalation:	Can cause CNS depression. May cause headaches and dizziness. Prolonged or repeated exposure may cause liver and kidney damage.
Skin Contact:	May cause moderate skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin resulting in skin irritation and dermatitis.
Eye Contact:	Mildly irritating to the eyes
Ingestion:	Harmful or fatal if swallowed. Pulmonary respiration hazard. While ingesting or vomiting, may enter lungs and produce damage. May produce CNS effects, which include dizziness, loss of balance and coordination, or unconsciousness. Irritating to mouth, throat, and stomach.
Target Organs:	Central nervous system, skin, eyes, liver, kidneys

ACUTE TOXICITY

General Information: Water based material with small amounts of methanol and toluene, which can have toxic effects in large quantities.

Component Analysis:

Toluene (108-88-3):
Oral LD50 Rat: 2600-7500 mg/kg
Dermal LD50 Rabbit: 12124 mg/kg
Inhalation (mouse): 8000 ppm (4-hr dose)
Methanol (67-56-1):
Dermal LD50 Rabbit: 12800 mg/kg
Inhalation (rat): 64000 ppm (4-hr dose)

CARCINOGENICITY

General Information: This product is not classified as a carcinogen or potential carcinogen by OSHA, NTP, ACGIH, or IARC. No specific data available.

Component Analysis:

Toluene (108-88-3):
IARC: 3 – Unclassifiable as to Carcinogenicity in Humans
ACGIH: A4 – Not classifiable as a Human Carcinogen

CHRONIC TOXICITY

No data is available on mutagenicity, reproductive effects, or developmental effects.

SECTION 12. ECOLOGICAL INFORMATION

Components may be harmful to aquatic organisms and may cause long term effects in the aquatic environment.

Do not empty into drains or waterways.

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of waste in accordance with Federal, State, and local environmental control regulations. This material may be classified as hazardous under the Resource Conservation and Recovery Act. (40 CFR 261)

SECTION 14. TRANSPORTATION INFORMATION

This product is hazardous for transportation.

Shipping Name: Combustible liquid, n.o.s. (contains toluene, methanol)

Class: 3 Packing Group: III ID No.: NA1993 NAERG: 128

SECTION 15. REGULATORY INFORMATION

SARA Title III: Health: Acute YES Chronic YES EHS NO
Physical: Fire YES Reactivity NO Pressure NO

SARA 313 (TRI): This product contains the following chemicals subject to reporting under Superfund Amendments Reauthorization Act, Title III, Section 313 (Toxic Release Inventory):

<u>Component</u>	<u>% by weight</u>
Toluene (CAS# 108-88-3)	3-10 %

California Proposition 65:



WARNING: This product can expose you to toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. No warranty of merchantability or any other warranty, expressed or implied, is given. In no case shall the information provided herein be considered a part of the terms and conditions of sale. Seaman Corporation assumes no obligation or liability for the information given or results obtained. All materials may present unknown hazards and should be used with caution. Final determination of suitability of any material is the sole responsibility of the user.

For questions related to the safety of this product, e-mail msds@seamancorp.com or call (330) 262-1111

FiberTite® is a registered trademark of Seaman Corporation.



Innovative Customer Solutions through Fiber and Polymer Technology

1000 VENTURE BLVD. ▪ WOOSTER, OHIO 44691
PHONE: (330) 262-1111 ▪ FAX: (330) 263-6950 ▪ www.seamancorp.com