



FTR 601-ECO

Product Data

FTR 601-ECO Fleece-Back and Insulation Adhesive is a dual component low-rise polyurethane foam adhesive that is VOC free, contains no solvents, and sets in minutes.

DESCRIPTION

FTR 601-ECO is a dual use adhesive for fleece-back membranes in spatter applied applications and a variety of insulation and other substrates in traditional bead-applied installations. FTR 601-ECO sets in minutes, and application is quick and easy, resulting in significant labor savings for the contractor.

FTR 601-ECO expands and rises to fill minor surface irregularities, regardless if used in spatter or bead-applied. FTR 601-ECO comes in 5.8 gallon canisters.

INSTALLATION/APPLICATION

Please refer to FiberTite.com for the full application instructions for FTR 601-ECO and FiberTite Roof System products. Please coordinate with the FiberTite Technical Team for any roof design questions prior to installation.

APPROVED MEMBRANES*

All FiberTite Fleece-Back Membranes

*SPATTER APPLICATION ONLY

APPROVED SUBSTRATES

- FTR-Value Insulation
- Approved Polyisocyanurate Insulation
- Approved extruded polystyrene Insulation (XPS)
- Approved expanded polystyrene Insulation (EPS)
- Gypsum Cover Boards
- Cement Boards
- Modified Bitumen Membranes
- Gypsum
- Structural Concrete
- Lightweight Insulating Cellular Concrete
- Smooth BUR

PHYSICAL PROPERTIES

Color	Light Amber
Physical State	Viscous Liquid / Catalyzed to Cellular Foam
Solid Weight	NA / High Solid Content
Application	2-component containers, Part 1 and Part 2, should yield approximately:
Bead Applied	Ribbon Application Coverage Rate is up to 35 square/set.
Spatter	Spatter Application Coverage Rate is up to 24 square/set.
Open/Cure Time	5-8 Minutes
Shelf Life	12 Months
Working Temperature Range	40°F (4°C) and rising
Storage	70°F + (21°C+) for a minimum of 48 hours prior to use and remain in a warm storage area until ready for use on the rooftop



For more information on FiberTite Systems and accessories please call:
Seaman Corporation (800) 927-8578
International (330) 262-1111
www.FiberTite.com

FiberTite® is a registered trademark of Seaman Corporation.

These specifications are current as of the date of printing. Revisions or additions may be issued periodically. For a listing, presentation, and download of the most recent data, visit:

www.FiberTite.com/document-library/product-data-sheets



Subject to the conditions of Approval for a roof covering when installed as described in the current edition of the Approval Guide.



As to an external fire exposure only. See UL directory of products certified for Canada and UL roofing materials and systems directory 34KL, 48PO, 97P9.